ACS International, Inc.—SDS

Artistone™ Last Revised: 1/7/2022 Print Date: 1/7/2022

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade name: Artistone; includes all product colors. General use: Cultured granite filler material.

Manufacturer Name Emergency Information

ACS International, Inc. 4775 S. Third Avenue Tucson, AZ 85714 Tel: 520.889.1933

Emergency Telephone: 1-800-669-9214 Direct: 520-889-1933 M-Th 7am to 4 pm, F 7 to 11 am

2. HAZARDS IDENTIFICATION

Most Important Hazards: This product may irritate eyes and skin upon prolonged or repeated exposure. Inhalation of high

concentrations of dust may produce irritation of the respiratory tract. Not considered to be toxic.

Specific Hazards: There is no known effect from chronic exposure to this product.

Potential health effects

Primary routes of exposure: Eye Contact—Yes; Inhalation—Yes; Skin—Yes; Ingestion—No; Skin Absorption—No

Symptoms of acute overexposure:

Skin: Not a known skin irritant. Eyes: Irritant by mechanical means.

Inhalation: Inhalation of dust may produce respiratory tract irritation, characterized by burning, sneezing and

coughing. Considered a nuisance particle.

Ingestion: Not applicable under normal industrial situations

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Abbr.	CAS No.	EIN	Weight %	ECC No.	Class	ACGIH	OSHA	Other Limits
			No.				TLV	PEL	
Calcium	CaCO ₃	21645-51-2		80-60%					15 mg/M3 (total dust)
carbonate									5 mg/M3 (resp)
Filler*		Various		20-40%					15 mg/M3 (total)

^{*}Filler is proprietary, trade secret ingredient and is considered non-hazardous under OSHA 29 CFR 1910.1200.

4. FIRST AID MEASURES

Skin: Not a skin irritant.

Eyes: May cause eye irritation. If contact lenses are present, remove. Immediately flush

eyes with running water for a minimum of 15 minutes. Seek medical attention if irritation persists.

Inhalation: Inhalation of dust may produce respiratory tract irritation, characterized by

burning, sneezing and coughing. Remove individual to fresh air and allow to rest. Obtain medical assistant

is breathing remains labored.

Not applicable under normal industrial situations. Give large quantities of water to Ingestion:

induce vomiting. Seek medical attention.

5. FIRE FIGHTING MEASURES

Water—Yes **Extinguishing Media:** Carbon Dioxide—Yes Dry Chemical—Yes Foam—Yes

> Alcohol Foam—No Use a self-contained breathing apparatus approved by NIOSH for all fires.

ACS International, Inc.—SDS

Artistone[™]

PAGE: 2 of 3

Last Revised: 1/7/2022

Print Date: 1/7/2022

Flash Point: N/A
Explosive limits in air: N/A
Unusual Fire and Explosion Hazard:

Generally non-flammable. In a sustained fire, product components may degrade to form carbon

monoxide, hydrogen cyanide, and other hazardous byproducts.

NFPA Classification: Flammable: 0 Health: 0 Reactivity: 0 Specific Hazards: 0

6. ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Wear appropriate personal protective equipment.

Spill Control: For small spills vacuum or scoop-up material for recovery or disposal in a sanitary landfill.

Avoid dust producing conditions and use good ventilation.

7. HANDLING AND STORAGE

Handling precautions:

Avoid direct contact with eyes. Do not breathe dust in concentrations above established limits. After handling, always wash hands thoroughly with soap and water before eating, drinking, or smoking. Use process enclosures, local

exhaust ventilation, or other engineering controls to keep airborne levels low.

Storage:

Store in a dry, cool and well ventilated area. Avoid damaging storage containers.

Storage color code: Orange, general storage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Store/use in a well ventilated area. Mechanical ventilation is recommended.

Personal Protection Equipment

Respiratory: Wear a NIOSH approved filtering face piece dust mask wear ventilation is not adequate with particulate filters in

atmosphere to 10X the PEL. Use in a well ventilated area.

Eye: Safety glasses with side shields are recommended.

Skin: Where skin exposure is likely to occur, long sleeved clothing is recommended. Gloves are also recommended. May

cause dry irritated skin.

Exposure Limits: See Section 2.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Granular solid. Color: Various Odor: None

Specific Gravity: N/A Boiling Point: N/A Melting Point: 1517° F (825° C)

Solubility: 0.001 gm in 100 ml water, soluble in dilute acids.

10. STABILITY AND REACTIVITY

Stability: This product is stable under ordinary conditions. **Incompatibility:** Acids, fluorine, magnesium with hydrogen.

Decomposition: In a sustained fire, calcium carbonate can produce calcium oxide fumes and liberates carbon dioxide.

11. TOXICOLOGICAL INFORMAITON

Significant Routes of Exposure: Inhalation. Not a known carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Low toxicity for humans or animals under normal conditions of use. This product is water soluble.

ACS International, Inc.—SDS

Artistone[™]

PAGE: 3 of 3

Last Revised: 1/7/2022

Print Date: 1/7/2022

13. DISPOSAL CONSIDERATIONS

Waste disposal or recycling: Recover and place material in a suitable container for intended use or disposal. Recycle when possible.

14. TRANSPORT INFORMATION

DOT/TDG Classification: Not controlled.

15. REGULATORY INFORMATION

Other Regulations: Some or all of the reportable chemical substances in this product are regulated by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

R-phrases: R36, Irritating to eyes. R42, May cause sensitization by inhalation.

S-phrases: S22, Do not breathe substance. S25, Avoid contact with eyes.

16. OTHER INFORMATION

National Fire Protection Association (USA) Ratings:

Health: 0 Flammability: 0 Reactivity: 0

Store in a cool, dry, well-ventilated area. Keep containers closed. Prolonged exposure to moisture will lead to caking of the product. No hazard entailed, but will result as a detriment in handling.

Dissolves in strong acids.